




## FLH WINDSCREEN TRIM

HOLESHOT

MERC

SCALLOP



### PERFORMANCE MACHINE LIMITED WARRANTY INFORMATION

Performance Machine warrants to the original purchaser that the parts of this windscreen trim to be free of manufacturing defects in materials and workmanship for a period of one (1) year from the date of purchase. In the event warranty service is required, you must call Performance Machine immediately with a description of the problem.

If it is deemed necessary for Performance Machine to make an evaluation to determine whether the part is defective, a return authorization number will be given by Performance Machine. The parts must be packaged properly so as to not cause further damage and returned prepaid to Performance Machine with a copy of the original invoice of purchase and a detailed letter outlining the nature of the problem. If after the evaluation by Performance Machine the part was found to be defective it will be repaired or replaced at no cost to you. If we replace it, we may replace it with a reconditioned one of the same design.

Performance Machine shall not be held liable for any consequential or incidental damages resulting from the failure of a Performance Machine part.

Performance Machine shall have no obligation if a part becomes defective as a result of improper installation or abuse.

## PM FLH WINDSCREEN TRIM INSTALLATION

1. Place motorcycle securely on a lift or on the sidestand.
2. Using a T27 Torx driver, remove the 3 factory bolts holding the windscreen.



3. Place the PM windscreen trim onto the fairing and install the supplied 1/4" button head center bolt and leave loose. Install the outer 2 bolts and torque to 20-30 in-lbs.



4. Hit the road!